

SoundStep

XLPE Acoustical Grade Underlayment **XL**

For use under Floating Engineered Wood, Laminate and Glue-Down Wood Floors



specifications

SoundStep underlayment is one of the most efficient and affordable flooring underlayments available, and has high acoustical performance. Condo, Townhome and Homeowners Association Approved.

Thickness: 2mm
Density: 5# (+/-10%)
WVTR (Water Vapor Transmission rate): 0.15 lbs/1000 Sq.Ft./Day

Sound specifications:
ASTM E2179-03 Delta IIC 23

Standard roll sizes:
48" x 25' (100 sf)
15 rolls per box, 8 boxes per pallet
120 rolls per pallet, 26 pallets per truck

advantages

- **Excellent sound rating: Delta Δ sound rating = 23**
- **Exceeds requirements for moisture vapor transmission**
- **Superior compression characteristics to support click-together system**
- **Reduces reflective noise & floor sound transmission**
- **Can use over concrete and wood subfloors**
- **Suitable over radiant heated floors**
- **Features lip & tape for easy and fast installation**
- **Eliminates minor subfloor imperfections**
- **Humidity, mold & mildew resistant**

installation

- Subfloor surface must be clean and dry before installation.
- Start in a corner. Unroll underlayment over subfloor with Film Lip overlapping it down against the subfloor.
- Roll out next row in the same manner butting foam close to first row and covering Edge Seal overlapping lip. Do not overlap foam pad just the FilmLip overlapping.
- Secure the Film Lip overlapping to it. Continue with installation. Seal all open seams with aggressive adhesive plastic tape.
- Install flooring per manufacturers instructions.