

COVER II

Hard Surface Protective Foam



48"x200' (800 Sq. Ft.)

Cover provides surface protection for newly installed floors to prevent scratching & denting. Cover is breathable and will release moisture under the surface and resist surface spills and water spots on the top of the film surface.

A D V A N T A G E S

Water & Oil Resistant:

Cover protects from stains, oils and chemicals

Puncture Resistant:

Cover has a special blended film layer that is tear resistant

Aerated:

Cover is perforated with vent holes to lock out water and spills but allow the material to release trapped moisture

Lays Flat:

Cover is a ridged foam which lays flat to lessen the risk of tripping or stumbling on the floor



I N S T A L L A T I O N I N S T R U C T I O N S

- Before rolling out Cover, be sure to sweep, vacuum, and remove debris from the finished flooring surface.
- Roll out Cover over the finished flooring surface. Always install with the aerated film layer up.
- Use duct tape to connect or splice the rolls across the room. If using Cover with Self Sealing tape, simply join the extended film lip to the other end of the next roll by peeling off the liner of the adhesive tape and adhering it to the extended film lip.
- Always be sure to connect the rolls together evenly so that the foam is not overlapping each other and there are no wide gaps between the foam.
- Cover is reusable, simply roll up and take to the next job!

