

ValueWalk

HIGH PERFORMANCE UNDERLAYMENT FOR FLOATING FLOORS



For use as underlayment for laminate and floating wood floor installations

ValueWalk underlayment is one of the most efficient and affordable flooring underlayments available. ValueWalk is acoustically superior to most underlayments. Condo, Townhome and Homeowners Association Approved.

- Offers protection and comfort for underneath all brands of applicable flooring.
- Softens and insulates noise.
- Economical, cost efficient.
- Superior water and moisture protection.

PRODUCT SPECIFICATIONS

2mm Thickness 3.1# Density

Impact Sound Transmission:

ASTM E492-96, ASTM E989-89 Impact Insulation Class (IIC) = 71 (6" concrete with ceiling assembly, in a controlled environment.)

Sound Transmission Loss:

ASTM E90-99, ASTM E413-87 Sound Transmission Loss (STC) = 67 (6" concrete with ceiling assembly) Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Classification for Rating Sound Insulation to measure the sound insulation properties of the test specimen, in a controlled environment.

WVTR .446 lb. per 1,000 sq. ft. / day

Sub-Floor Requirements:

- Maximum 1/4" variance in 10'.
- Must be properly prepared per NALFA specifications.
- All cracks in excess of 1/16" must be filled.
- Surface must be clean, dry and free of contaminants.

Installing ValueWalk:

1. Roll the underlayment out and trim to fit the floor using a sharp utility knife and a straight edge.
2. Be sure to run the underlayment to the edges of the perimeter leaving no gaps.
3. Seams should be butted together, leaving no gaps or overlaps.

Flooring Material Installation:

Install flooring material as per flooring manufacturers and NALFA recommendations.

